

POWER HACKSAW BLADES

HSS BIMETAL / HSS FULL HARD

- ☆ For general purpose cut-off operation
- ☆ The no. of teeth is the std no. supplied for general purpose working.
- ☆ TPI: 10T / 8T / 6T / 4T
- ☆ Standard No.: GB/T 6080—1998 / ISO 2336.2—1996

SAW



Order No.	Ø L (mm)	Ø W (mm)	T (mm)			Order No.	Ø D (mm)	Ø B (mm)	T (mm)
300025125	300	25	1.25			12100125	12"	1"	1.25
350025125	350	25	1.25			14100125	14"	1"	1.25
400025125	400	25	1.25			16100125	16"	1"	1.25
350032160	350	32	1.6			14125160	14"	1-1/4"	1.6
400032160	400	32	1.6			16125160	16"	1-1/4"	1.6
450032160	450	32	1.6			18125160	18"	1-1/4"	1.6
400032200	400	32	2			16150180	16"	1-1/2"	1.8
450032200	450	32	2			18150180	18"	1-1/2"	1.8
500032200	500	32	2			18150200	18"	1-1/2"	2
400036160	400	36	1.6			20150200	20"	1-1/2"	2
400038180	400	38	1.8			21150200	21"	1-1/2"	2
450038180	450	38	1.8			24150200	24"	1-1/2"	2
450038200	450	38	2			20200250	20"	2"	2.5
500038200	500	38	2			24200250	24"	2"	2.5
530038200	530	38	2			26200250	26"	2"	2.5
600038200	600	38	2			28200250	28"	2"	2.5
400040200	400	40	2			30200250	30"	2"	2.5
450040200	450	40	2						
500040200	500	40	2						
600040200	600	40	2						
450045250	450	45	2.5						
550045250	550	45	2.5						
600045250	600	45	2.5						
500050250	500	50	2.5						
550050250	550	50	2.5						
575050250	575	50	2.5						
600050250	600	50	2.5						
650050250	650	50	2.5						
700050250	700	50	2.5						
750050250	750	50	2.5						
800050250	800	50	2.5						